

FIRENOCK/LIGHTNINGNOCK COMPARISON CHART

	FIRENOCK "G" Series GS	FIRENOCK "G" Series GC	FIRENOCK "G" Series GA	FIRENOCK "G" Series GE	FIRENOCK "G" Series S1	FIRENOCK "G" Series C1	FIRENOCK "G" Series ST	LIGHTNINGNOCK "G" LG
Price	Suggested Retail price in US\$							
	\$54.95	\$54.95	\$54.95	\$54.95	\$19.95	\$20.95	\$19.95	\$12.95
Date	Availability							
	Apr-08	Apr-08	Apr-08	Apr-08	Apr-08	Apr-08	Apr-08	Apr-08
	Last sold							
	Current	Current	Current	Current	Current	Current	Current	Current
Includes	# circuit housed in a custom molded nock							
	3 red	3 red	3 red	3 red	1 red	1 red	1 clear	1 orange
	3 425 Pin battery							
	425	425	425	425	425	425	425	425
	# Green matched weights practice nocks							
	3	3	3	3	2	2	2	Optional
	# O-rings for centering							
	3	30	NO	3	1	14	1	rubber band
	1 Nock tool							
	YES	NO	YES	YES	NO	NO	NO	NO
	1 1/8" thick 1/2" diameter ~35 gauss Magnet							
	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	1 3M VHB die cut double sided tape included							
	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Function	Brightness(1)							
	~450 LUX	~480 LUX	~500 LUX	~500 LUX	~450 LUX	~480 LUX	~450 LUX	~350 LUX
	Blinking Light to scare game							
	NO	NO	NO	NO	NO	NO	NO	NO
	Battery Pin Connector (-)							
	Gold plated	Gold plated	Gold plated	Gold plated	Gold plated	Gold plated	Gold plated	Tin plated
	Battery Wire Connector (+)							
	Ti alloy	Ti alloy	Ti alloy	Ti alloy	Ti alloy	Ti alloy	Ti alloy	Stainless
	Easton uni-bushing Compatibility							
	YES	NO	NO	NO	YES	NO	YES	YES
	Extended Battery (435 size) Compatibility							
	YES	YES	YES	YES	YES	YES	YES	YES
	Extreme Shock End Cap Compatibility							
	YES	NO	NO	NO	YES	NO	YES	YES
	Fits Shaft with Internal Diameter in Inches							
	0.242" - 0.246"	0.301" - 0.303"	0.202" - 0.204"	0.229" - 0.231"	0.242" - 0.246"	0.301" - 0.303"	0.242" - 0.246"	0.242" - 0.246"
	Focus Beam LED Spread Angle							
	15°	15°	15°	15°	15°	15°	15°	35°
	Glue for Installation							
	NO	NO	NO	NO	NO	NO	NO	NO
	Heat for Installation							
	NO	NO	NO	NO	NO	NO	NO	NO
	LED used (LUX at 1 cm with 3.3v)							
	8000 LUX	8000 LUX	8000 LUX	8000 LUX	8000 LUX	8000 LUX	8000 LUX	5000 LUX
	Light-pipe Lens							
	Built-In	Built-In	Built-In	Built-In	Built-In	Built-In	Built-In	Built-In
	Nock Length; Entire in Inches (mm)							
	1.216" (31)	1.024" (26)	0.94" (24)	0.94" (24)	1.216" (31)	1.024" (26)	1.216" (31)	1.216" (31)
	Nock Length; Exposed in Inches (mm)							
	0.67" (17)	0.227" (5.6)	0.43" (11)	0.43" (11)	0.67" (17)	0.227" (5.6)	0.67" (17)	0.67" (17)
	Nock Used							
	"S"	"C"	"A"	"E"	"S"	"C"	"S"	"S"
	Replaceable Battery							
	YES	YES	YES	YES	YES	YES	YES	YES
	Replaceable Nock							
	YES	YES	YES	YES	YES	YES	YES	YES
	Shrink Tube for Battery Holding							
	NO	NO	NO	NO	NO	NO	NO	NO
	Spin Balance at (100 RPM)							
	YES	YES	YES	YES	YES	YES	YES	YES
	Spin Balance at (500 RPM)							
	YES	YES	YES	YES	YES	YES	YES	YES
	Tolerance for Actuator Placement in Inches (mm)							
	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	Drop Tolerance							
	6' - 21' (2-7 M)	6' - 21' (2-7 M)	6' - 21' (2-7 M)	6' - 21' (2-7 M)	6' - 21' (2-7 M)	6' - 21' (2-7 M)	6' - 21' (2-7 M)	6' (2M)
	Shock Tolerance (up to)							
	150g	150g	150g	150g	150g	150g	150g	30g
	Battery Life (Continuous Burn)							
	20-32 hours	20-32 hours	20-32 hours	20-32 hours	20-32 hours	20-32 hours	20-32 hours	16-24 hours
	Battery Life (1-hour Burns)							
	36-48 times	36-48 times	36-48 times	36-48 times	36-48 times	36-48 times	36-48 times	20-28 times
	Weight with Nock							
	~27 grain	~31 grain	~24 grain	~25 grain	~27 grain	~31 grain	~27 grain	~27 grain
Warranty	30 days	30 days	30 days	30 days	30 days	30 days	30 days	DOA

(1) the brightness was measured with Digital Lux Meter (model LX1010B), Serial #S501233, at 0.0 cm distance with provided battery (assume fresh) at the tip of the nock with 3 samples' average. The Information contained herein is subject to change without notice.

REFRESH/UPGRADE SERVICES

A no hassle/no questions asked refresh service is what we believe Firenock users prefer after the warranty period had ended. Firenock™ brand lighted nocks are eligible for refresh and Lightning Nock™ brand lighted nocks are eligible for upgrade. Your old Firenock / Lightning nock circuit(s) and polycarbonate nocks can be refreshed / upgraded and you can get working Firenock circuit(s), and new polycarbonate nock(s) with a small service fee. This service is only valid when funds are sent along with the lighted nock(s) and circuit(s). This service is subject to change without notice and can be terminated at anytime. This service will begin on 6/1/2008 or 60 days after the initial shipment of Firenock LLC's Firenock "G" series lighted nock, which ever comes last.

Refresh Services Procedures:

Please send in your old Firenock/Lightning nock circuit(s) and polycarbonate nocks with funds to us (see below for service fee). Please do not send any of the O-rings and batteries. We cannot be responsible for anything that is not part of the refresh service. If the style of Firenock you want to refresh is no longer available, standard Firenock ("S" style) will be substituted. Shipping and handling is included in the service fee for this refresh service.

Note: One can easily differentiate Firenock and Lightning Nock by the color of battery pin connector on the circuit board (Firenock is gold while Lightning Nock is silver).

The service fee for refresh service is as follows

(Shipping and handling charge is included):
 \$10.00 for 1 piece Firenock
 \$12.00 for 1 piece Lightning Nock
 \$25.00 for 3 pieces Firenocks
 \$33.00 for 3 pieces Lightning Nocks

Additional accessories can be purchase at the following price alone with the refresh service without incurring shipping and handling fee:
 \$9.95 for 3 of batteries
 \$2.00 for 3 sets of O-rings

This service is only available in USA.

Firenock™

The Most Advanced Lighted Nock

Gold GOLD PLATED CONNECTOR FOR RELIABILITY

SPIN BALANCED, RATTLE PROOF

SHOCK AND KNOCK PROOF

VISIBLE UP TO 65 YARDS IN DAY LIGHT

EXTREMELY LIGHT WEIGHT, ~27 GRAINS

24 HOURS ULTRA LONG LASTING

LED FOCUS BEAM LED

FREE HAND, NO TOOLS FIELD INSTALLATION

WEATHER PROOF HOUSING-LESS DESIGN

TURNS ON EVERY SHOT

NOCK FIELD CHANGEABLE

BATTERY FIELD CHANGEABLE

FIRENOCK Brand Product
 GS, for standard size carbon arrows
 ST, for standard size carbon arrows for Target
 GC, for standard size carbon arrows
 GA, for slim size carbon arrows
 GE, for medium size carbon arrows

LIGHTNING NOCK

THE MOST ADVANCED LIGHTED NOCKS
 FIRENOCK TECHNOLOGY FOR THE BUDGET ARCHER

LIGHTNING NOCK Brand Product

Lightning Nock G (LG),
 for standard size carbon arrows

NOCK FIELD CHANGEABLE

BATTERY FIELD CHANGEABLE

VISIBLE UP TO 55 YARDS IN DAY LIGHT

SUPER LIGHT WEIGHT, ~27+ GRAINS

16 HOURS SUPER LONG LASTING

NEW! FOR 2008

>>> NO MAGNET REQUIRED
 >>> (ULTRA SMART "G" SWITCH EQUIPPED)
 >>> IPX8 SALT WATER PROOF ADAPTOR

